

ID BANDER STEEL & ALUMINUM

WITH AUTOMATIC EDGE PROTECTOR **APPLICATORS FOR OD & ID APPLICATION**



SPECIFICATIONS

PACKAGE DIMENSIONS:

OD: 35"-84" ID: 20"-24" WIDTH: 24"-73" EDGE PROTECTION: ID & OD STRAP DIRECTION: ID COIL TEMP: Cold

AUTOMATION CONTROL: Siemens / Allen Bradley

OPERATOR INTERFACE: Siemens / Allen Bradley

UNIQUE FEATURES

HOT & COLD COILS Ability to strap hot or cold coils.

STRAP PLACEMENT Capable of placing multiple straps.



SWORD VERSATILITY Movable sword allows for various

custom applications.

and inline indexing.



MACHINE POSITIONING Possible to have an assortment of positions including online,

offline, maintenance position,

1 **STRAPPING HEAD**

Single or dual strapping head located either on the top or side of the machine.

κЯ **COIL ORIENTATION** 2.24 Coils can be presented Eye parallel or perpendicular to travel.

CUSTOMIZED TO SUIT YOUR NEEDS

We work with customers to design a machine that will help them succeed. Our commitment to deliver what is needed in a strapping machine, whether it is a custom fit, custom solution or a standard machine, keeps businesses running smoothly and on time.