



TOP SEAL

WOOD PANEL PRODUCTS

01 SPECIFICATIONS

PRODUCT TO BE STRAPPED:

Stacked bundles

PACKAGE DIMENSIONS:

Min/Max Width; 48"-72"

Min/Max Length; 48"-145"

Min/Max Height; 16.5"- 32"

STRAP DISPENSER:

350 lbs Powered Strap Dispenser

PLC & INTERFACE:

Allen Bradley/ Siemens



STRAP CYCLE TIME (TARGET):

Cycle Time: 90 seconds to apply 5 straps for packages > 26" High.

Cycle Time: Up to 96 seconds for packages < 26" High

Side compression not included in cycle time.

DUNNAGE FEEDERS:

Bottom dunnage feeder

Width [Min/Max]; 3"

Height [Min/Max]; 3"

Length [Min/Max]; 48"-61"

STRAPPING PATTERN:

3-6 straps per package

02 UNIQUE FEATURES



TOP EDGE PROTECTION
Electric Actuators



INTEGRATION
Quick and easy integration to new or already installed lines.



STRAPPING HEAD
Plastic Strapping Head



POWER
Hydraulic or Electric



DUNNAGE
Optional robotic pallet feeder.



TOP AND SIDE COMPRESSION
Fully adjustable



03 CUSTOMIZED TO SUIT YOUR NEEDS

We work with customers to design a machine that will help them succeed. Our commitment to deliver what is needed in a strapping machine, whether it is a custom fit, custom solution or a standard machine, keeps businesses running smoothly and on time.



Top Seal Wood Products